

Advantages

Vorteile // Avantages // Ventajas // Voordelen

Different contemporary embossings
Verschiedene zeitgemässe Prägungen
Différents gaufrages contemporains
Vários acabados contemporâneos
Verschillende hedendaagse embossings

Flame retardant
Flammhemmend
Ignifuge
Ignífugo
Vlamvertragend

100% block out
100% super undurchsichtig
100% super opaque
100% super opaco
100% super opaak

Highly UV resistant
Sehr UV-beständig
Très résisant aux UV
Muy resistente a los UV
In hoge mate UV-bestendig



Pergola



tent, pergola
& military

CAT02004INT261

Technical specifications

Technische Daten // Données techniques // Datos técnicos // Technische specificaties

	B8115 Block out	B8118 Cube embossing
Total Weight - ISO 2286/2:2016 Gesamtgewicht // Poids total // Peso total // Totaal gewicht	850 g/m²	
Composition Zusammensetzung // Composition // Composición // Samenstelling	PES + PVC	
Fabric (Warp / Weft) - DIN ISO 2060:1994 Gewebe // Tissu // Tejido // Weefsel	PES, 1100 dtex PES, 1100 dtex	
Lacquering Lackierung // Laquage // Tipo lacado // Lacquering	Top: dull non marring Bottom: dull	Top: glossy Bottom: glossy
Breaking Strength (Warp / Weft) - ISO 1421/1:2016 Höchstzugkraft // Résistance rupture // Resistencia a la tracción // Treksterkte	2500 N/5cm 2300 N/5cm	
Tear Strength (Warp / Weft) - DIN 53363:2003 Weiterreisskraft // Résistance à la déchirure // Resistencia al desgarro // Scheurweerstand	270 N 270 N	
Adhesion - ISO 2411:2017 Haftung // Adhérence // Adhesión // Hechting	100 N/5cm	
Temperature resistance - EN 1876/1:1998 Temperaturbeständigkeit // Tenue à la température // Resistencia térmica // Temperatuurbestendigheid	-40/+70 °C	
Light Fastness - ISO 105 B02:2014 Lichtechtheid // Tenue à la lumière // Solidez color // Lichtechtheit	7-8	
Fire Behaviour Brennverhalten // Reaction au feu // Resistencia al fuego // Brandgedrag	(UNI 8456 - 9174) ADR Cl. II	(NF P92-507:2004) M2
Reaction to Fire - EN 13501-1:2018 Reaktion auf Feuer // Réaction au feu // Reacción al fuego // Reactie op vuur	B-s2,d0	



Registration,
Evaluation,
Authorization
and restriction
of Chemicals



Recyclable fabric
Recyclables Textilien
Textiles recyclables
Productos reciclables
Recycleerbaar textiel



Slitting (width) on request
Schneiden (Breite) auf Anfrage
Tronçonnage (largeur) sur demande
Cortar (ancho) bajo pedido
Snijden (breedte) op aanvraag



Sustainable options available
Nachhaltige Optionen verfügbar
Options durables disponibles
Opciones sostenibles disponibles
Duurzame opties beschikbaar



Go to sieline.com for more information.
Fabriekstraat 23 - 8850 Ardoole - Belgium
+32 (0) 51 740 900 - info@sieline.com - sieline.com

Produced in Belgium & France in ISO 9001:2015 certified plants

All our technical characteristics are indicative. Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. All Sieline products comply with the Reach Regulation 1907/2006/CE. Last modified: 26 februari 2026 1:11 p.m.



Pergola



Adding that extra touch of luxury



Different
contemporary
embossings



100% block out



Flame retardant



Highly UV
resistant

B8115 // B8118

NEOS


NEOS

B8115

Block out // Super undurchsichtig // Super opaque // Super opaco // Super opaak



1932
300 cm



7278
300 cm



7315 NEW
300 cm



7363 NEW
300 cm



8103 NEW
300 cm





9002
300 cm


Other colours on request // Andere Farben auf Anfrage // Autres coloris sur demande // Otros colores bajo pedido // Andere kleuren op aanvraag

B8118


Cube embossing // Würfelprägung // Gaufrage en cube // Acabado en cubo // Kubus embossing




1622
300 cm



7024
300 cm



7340
300 cm



7500
300 cm



9002
300 cm

Other colours on request // Andere Farben auf Anfrage // Autres coloris sur demande // Otros colores bajo pedido // Andere kleuren op aanvraag

